



Ref. Certif. No.

US-32102-A1-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

AC/DC Power Supplies

Name and address of the applicant

QUALSTAR CORPORATION
130 W COCHRAN ST, SUITE C
SIMI VALLEY CA 93065 USA

Name and address of the manufacturer

N2POWER INC., A SUBSIDIARY OF QUALSTAR CORPORATION
130 W COCHRAN ST, SUITE C
SIMI VALLEY CA 93065 USA

Name and address of the factory

Note: When more than one factory, please report on page 2

WANWANG ELECTRONICS (SHENZHEN) CO., LTD
NO.20 YUANGHU RD ZHANGBEI AILIAN LONGGANG DISTRICT SHENZHEN, GUANGDONG, 518172 CHINA

Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark (if any)



Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

XL375-12 CS S148, XL375-xx @
See Page 2

Additional information (if necessary may also be reported on page 2)

The report was revised to include administrative modifications.

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

E211115-A6002-CB-2 issued on 2019-01-24,
E211115-A6002-CB-2 issued on 2019-01-29

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-01-30
Original Issue Date: 2018-07-19

Signature:

Jolanta M. Wroblewska



Ref. Certif. No.

US-32102-A1-UL

Model Details:

XL375-xx @,

where "xx" denotes the output voltage (V1) between 12-60 Vdc and @ may be any alphanumeric character or blank, for marketing purpose only and no impact safety related constructions and critical components. May be followed by LED indicated changes in secondary circuit, see Model Difference for explanation.

Ratings:

Input:

100-277 Vac, 4.5 A, 47-63 Hz

- or -

100-240 Vac, 4.5 A, 47-63 Hz

Output:

V1 = designated by "xx" in model nomenclature

A1 = 358 Watts/V1 A

V2 = 12 Vdc

A2 = 1 A

V3 = 5 Vdc (stand-by)

A3 = 1 A

Additional Information:

Additionally evaluated to EN 62368-1:2014 / A11:2017; National Differences specified in the CB Test Report.

The original Report was modified to include the following administrative changes:

Amendment:

- Removed Panyu Trio factory.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-01-30

Original Issue Date: 2018-07-19

Signature:

Jolanta M. Wroblewska